



## ROLL LABEL DIVISION

Seal and Reseal

Issue Date: 08/16/2018  
Date last modification 08/16/2018

Product code: 4-RL2D-08642

## RI-707/3.5 PP GLOSS WHITE TC AR827B WG2.1

### Applications

Seal and Reseal labels for wet packed products like baby wipes, cosmetics and household products. Prior to its use it is necessary to check compatibility between the adhesive and the content of the packages, and between the adhesive and the substrate.

### Face Material

<b>Type</b>	Top coated polypropylene	
<b>Color and Finish</b>	White gloss	
<b>Weight</b>	88 g/m <sup>2</sup> ±10%	ISO 536
<b>Thickness</b>	3.5 mil ±10%	ISO 534-80

### Adhesive

Acrylic removable adhesive featuring high resistance to moisture, Soft peel adhesion, suitable for seal and reseal labels on wet packed products (like baby wipes or cosmetic wipes). This adhesive is approved by Isega (Direct contact dry & moist, non-fatty foodstuffs) according to German recommendations XIV and complies with FDA 175.105 (indirect food contact).

<b>Reference</b>	AR827B	
<b>Type</b>	Acrylic removable	
<b>Min. Appl. Temperature</b>	50°F	
<b>Service Temperature</b>	-22°F / +212°F	
<b>Shear</b>	High	
<b>Tack</b>	1.3 Lb/inch	FINAT FMT9
<b>Final Adhesion</b>	0.4 Lb/inch	FINAT FTM2

### Liner

<b>Type</b>	One side siliconized supercalendered Glassine	
<b>Color and Finish</b>	White	
<b>Weight</b>	60 g/m <sup>2</sup> ±10%	PP-032 - ISO 536
<b>Thickness</b>	2.1 mil ±10%	ISO 534
<b>Transparency</b>	>50 %	DIN 53 147-64

### Printing Methods

Printable with UV flexo, UV letterpress, UV screen-printing gravure and hot stamping.  
Testing for suitability between media, printers and inks is always recommended prior to use.

### Shelf Life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the under storage conditions as defined by FINAT section 2.5:

- Ideal storage conditions are at a temperature of 68–77°C and 40–50 % HR.
- Store in a cool and dry place.
- Do not store close to a heat source or in direct sunlight.
- Keep the material in the original packaging until required for use.

Pay particular attention to the recommended shelf-life and ensure correct stock rotation.



### Disclaimer

*All Ritrama's products are subject to manufacturing controls in order to guarantee the good quality of the products. The statements, technical information, data, values and recommendations regarding Ritrama's products are based on research and tests we believe to be reliable, but do not constitute a guarantee or warranty of whatsoever nature.*

*Considering the multiple uses of Ritrama's products, the user is recommended to test the products prior to their use, so to determine and ascertain the suitability and performance of the product for its intended application and purpose.*

*The methods of conversion and application of Ritrama's self-adhesive materials are multiple and it is therefore essential that the users are aware of the particular method to be used, prior to commencing the production.*

*Printing: Testing for compatibility between product, printers and inks is always highly recommended before printing the product.*

*Application Systems and Conditions: it is recommended that the performance of the product be always tested in the actual applications conditions as substrate state (rough, smooth, flat or irregular shapes, moderate curves, with or without rivets); applicator technology (hand application or fully automated lines); specific stress on Ritrama material once applied (high and/or low temperature, mechanical stress, exposure to challenging environment conditions), et cetera.*

*As Ritrama's products are used in conditions beyond its control, such as those listed above as example, Ritrama does not assume any liability for inappropriate use of the products.*

*Ritrama reserves the right to modify at any time and without the need of a prior notice, at its sole and exclusive discretion, the products, their features and technical specifications.*

*All Ritrama's products are sold subject to Ritrama's general terms and conditions of sale listed in the following Ritrama's web page: <http://www.ritrama.com/en/sale-conditions/>*